

Accessories

SILCAVER 55 tapes and sealing cords for ovens

SILCAVER 55 tapes are used in different applications for thermal separation or sealing. They are available in white and black colour. Furthermore, for easy assembling we also offer the tapes with an organic self-adhesive film on one side.

Standard dimensions

Thickness	2/3 mm
Roll width	10/20/50 mm
Roll length	50 m

The properties indicated are typical values obtained in serial testing and determined by acknowledged test methods. Product specific spreading of results should be taken into account. The indications do not represent guaranteed properties and cannot be used for any warranty claim. Subject to technical modifications.

SILCAVER sealing cords consist of e-glass and are available in different qualities, e.g. as braided cord with soft core in solid plaited packing (square or round). The softer knitted quality is mostly used in fireplaces and tiled stoves construction. It is available in white and black colour. A further quality is a twisted cord lace-made with brass wire.

Classification temperature 550 °C

Quality	Diameter	Length
Twisted cord lace-made with brass wire	6/8/10/12/15 mm	6 - 12 mm = 100 m
Knitted cord, black	6/8/10/12/15/20/25/30 mm	15 mm = 50 m
Knitted cord, untreated (white)		20 mm = 25 m 25 - 30 mm = 10 m

The properties indicated are typical values obtained in serial testing and determined by acknowledged test methods. Product specific spreading of results should be taken into account. The indications do not represent guaranteed properties and cannot be used for any warranty claim. Subject to technical modifications.

SILCA Service- und Vertriebsgesellschaft für Dämmstoffe mbH

Postfach 20 02 65, 40811 Mettmann | Auf dem Hüls 6, 40822 Mettmann
Telefon: +49 2104 9727-0 | Fax: +49 2104 76902 | info@silca-online.de | www.silca-online.de