

Accessories

SILCASIL 320 high-temperature silicone

SILCASIL 320 has an excellent adhesive strength and a **high temperature-resistance up to 320 °C**. It is used for sealing and bonding, e.g. for the bonding of cords or tapes. It can be applied on most firm, clean and dust-free surfaces, e.g. metal, ceramics or mineral materials. Exposure to high temperature is only permitted after complete hardening auf **SILCASIL 320**. The product is available in resealable tubes of 100 ml and cartridges of 310 ml.

Product details

Temperature resistance	max. 320 °C (1.000 h)
Density at 20 °C	1,15 g/cm ³
Hardness	20 Shore A
Working temperature	5 – 40 °C
Film formation on surface	after 10 minutes
Hardening, layer thickness 3 mm	after 24 h
Colour	grey
Packing unit	100 ml tubes; 310 ml cartridges

The properties indicated are typical values obtained in serial testing and determined by acknowledged test methods. Product specific spreading of results should be taken into account. The indications do not represent guaranteed properties and cannot be used for any warranty claim. Subject to technical modifications.



SILCA Service- und Vertriebsgesellschaft für Dämmstoffe mbH

Postfach 20 02 65, 40811 Mettmann | Auf dem Hüls 6, 40822 Mettmann

Telefon: +49 2104 9727-0 | Fax: +49 2104 76902 | info@silca-online.de | www.silca-online.de