

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.07.2015

Version number 2

Revision: 05.07.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **Date of compilation:** 10.04.2012
- **1.1 Product identifier**
- **Trade name:** SILCADUR Klebstoff 130
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the preparation:** refractory cement
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer / Supplier:**
SILCA Service- und Vertriebsgesellschaft für Dämmstoffe mbH
Auf dem Hüls 6
D-40822 Mettmann
Germany
Tel.: +49 (0)2104/9727-0
Fax: +49 (0)2104/9727-25
- **E-mail address of the competent person responsible for the Safety Data Sheet:** sdb@csb-online.de
- **Informing department:** Tel.: +49 (0)2104/9727-18
- **1.4 Emergency telephone number:** As above or next toxicological information centre

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS05 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
Silicic Acid, Sodium Salt
- **Hazard statements**
H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
- **Precautionary statements**
P261 Avoid breathing mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER/doctor if you feel unwell.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.07.2015

Version number 2

Revision: 05.07.2015

Trade name: SILCADUR Klebstoff 130

(Contd. of page 1)

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 1344-09-8	Silicic Acid, Sodium Salt	20 - 30%
EINECS: 215-687-4	☠ Eye Dam. 1, H318; ☠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335	
CAS: 1344-28-1	Aluminium oxide	70 - 80%
EINECS: 215-691-6	substance with a Community workplace exposure limit	

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**
Immediately remove any clothing contaminated by the product.
In case of irregular breathing or respiratory arrest provide artificial respiration.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness bring patient into stable side position for transport.
- **After skin contact:**
Instantly wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Rinse opened eye for several minutes under running water. Then consult doctor.
Remove contact lenses, if present and easy to do.
- **After swallowing:**
Rinse out mouth and then drink plenty of water.
Do not induce vomiting; instantly call for medical help.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Danger:** Danger of gastric perforation.
- **4.3 Indication of any immediate medical attention and special treatment needed** symptomatic treatment

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture**
Can be released in case of fire:
Irritant gases/vapours
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained breathing apparatus.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
If without risk possible, move drums with material away from dangerous area.

GB

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.07.2015

Version number 2

Revision: 05.07.2015

Trade name: SILCADUR Klebstoff 130

(Contd. of page 2)

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Avoid contact with skin and eyes.

Use breathing protection against the effects of fumes/dust/aerosol.

· **6.2 Environmental precautions:**

Do not allow to enter drainage system, surface or ground water.

Prevent material from reaching sewage system, holes and cellars.

· **6.3 Methods and material for containment and cleaning up:**

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Send for recovery or disposal in suitable containers.

Dispose of the material collected according to regulations.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Do not breathe vapour/spray.

Avoid contact with skin and eyes.

Make sure that all applicable workplace limits are observed.

· **Information about protection against explosions and fires:** No special measures required.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and containers:**

Store only in the original container.

Provide alkali-resistant floor.

Observe all local and national regulations for storage of water polluting products.

· **Information about storage in one common storage facility:**

Store away from foodstuffs.

Do not store together with acids.

Store away from metals.

· **Further information about storage conditions:**

Store container in a well ventilated position.

Store in cool, dry conditions in well sealed containers.

Protect from frost.

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **8.1 Control parameters**

· **Components with critical values that require monitoring at the workplace:**

1344-28-1 Aluminium oxide

WEL (Great Britain)	Long-term value: $10 \cdot 4^{**}$ mg/m ³ *inhalable dust **respirable dust
---------------------	---

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.07.2015

Version number 2

Revision: 05.07.2015

Trade name: SILCADUR Klebstoff 130

(Contd. of page 3)

- **8.2 Exposure controls**
- **Personal protective equipment**
- **General protective and hygienic measures**
Keep away from foodstuffs, beverages and food.
Instantly remove any contaminated garments.
Wash hands during breaks and at the end of the work.
Use skin protection cream for preventive skin protection.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
Do not eat, drink or smoke while working.
- **Breathing equipment:**
If all workplace limits are observed and good ventilation is ensured, no special precautions necessary.
- **Recommended filter device for short term use:** Filter P2
- **Protection of hands:**
Alkaline resistant gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Safety glasses
- **Body protection:**
Alkaline resistant protective clothing
Body protection must be chosen depending on activity and possible exposure.
- **Limitation and supervision of exposure into the environment**
Do not allow to enter drainage system, surface or ground water.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	viscous liquid
Colour:	white
Smell:	odourless
Odour threshold:	not applicable
- **pH-value at 20 °C:** 9 - 10
- **Change in condition**

Melting point/Melting range:	not determined
Boiling point/Boiling range:	not determined
- **Flash point:** not applicable
- **Inflammability (solid, gaseous)** not applicable
- **Ignition temperature:** not applicable
- **Decomposition temperature:** Not determined.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.07.2015

Version number 2

Revision: 05.07.2015

Trade name: SILCADUR Klebstoff 130

(Contd. of page 4)

· Self-inflammability:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive.
· Critical values for explosion:	
Lower:	not applicable
Upper:	not applicable
· Oxidising properties	not determined
· Vapor pressure:	Not determined.
· Density at 20 °C:	1.8 g/cm ³
· Bulk density:	not applicable
· Relative density	Not determined.
· Vapour density (AIR = 1):	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	not miscible or difficult to mix
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
dynamic:	not determined
kinematic:	not determined
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
Reacts with acids
Corrosive action on metals
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Acids
- **10.6 Hazardous decomposition products:**
Irritant gases/vapours
No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**

· **LD/LC50 values that are relevant for classification:**

1344-09-8 Silicic Acid, Sodium Salt

Oral	LD50	1100 - 1600 mg/kg (rat)
------	------	-------------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye damage.
- **inhalation:** May cause respiratory irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.07.2015

Version number 2

Revision: 05.07.2015

Trade name: SILCADUR Klebstoff 130

(Contd. of page 5)

- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability**
Anorganic product, is not eliminable from water by means of biological cleaning processes.
- **12.3 Bioaccumulative potential** Not bioaccumulative
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.
Water hazard class 1 (Self-assessment): slightly hazardous for water
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Disposal must be made according to official regulations.
- **European waste catalogue:**
Waste disposal key numbers from EWC have to be assigned depending on origin and processing.
- **Uncleaned packagings:**
- **Recommendation:**
Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.
Packagings that cannot be cleaned are to be disposed of in the same manner as the product.

SECTION 14: Transport information

- | | |
|--|-----------------|
| · 14.1 UN-Number
· ADR, IMDG, IATA | Void |
| · 14.2 UN proper shipping name
· ADR, IMDG, IATA | Void |
| · 14.3 Transport hazard class(es)
· ADR, IMDG, IATA
· Class | Void |
| · 14.4 Packing group
· ADR, IMDG, IATA | Void |
| · 14.6 Special precautions for user | Not applicable. |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.07.2015

Version number 2

Revision: 05.07.2015

Trade name: SILCADUR Klebstoff 130

(Contd. of page 6)

- | | |
|--|--|
| · Transport/Additional information: | Not dangerous according to the above specifications. |
| · UN "Model Regulation": | - |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **National regulations**
- **Information about limitation of use:** Employment restrictions concerning young persons must be observed.
- **Decree to be applied in case of technical fault:** Directive 2012/18/EU does not apply.
- **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

The(se) H-phrases are those of the ingredient(s) and do(es) not necessarily represent the classification of the product.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

- **Department issuing MSDS:**

C.S.B. GmbH Phone: +49 - 2151 - 652086-0

Düsseldorfer Str. 113 Fax: +49 - 2151 - 652086-9

47809 Krefeld / Germany

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

- **Sources:** These data are based on information submitted by pre-suppliers.